



Material Safety Data Sheet - Eco-Energy

MSDS ID NO.: 073010

Revision date: 07-30-2010

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product name: Eco-Energy Denatured Alcohol

Synonyms: Denatured Alcohol; Ethanol 98.5%

Chemical Family: Alcoholic solution

Formula: Mixture

Eco-Energy

725 Cool Springs Blvd. Suite 500

Franklin, TN

37067

Other information: 615-778-2898

Emergency telephone number: 615-778-2898 - CHEMTREC

2. COMPOSITION/INFORMATION ON INGREDIENTS

Denatured Alcohol is a mixture of ethyl alcohol and natural gasoline that is approved for use as an octane-enhancing blending component in gasoline.

Product information

Name CAS Number Weight % ACGIH Exposure

Limits:

OSHA - Vacated

PELs - Time

Weighted Ave

Other:

Eco-Energy Denatured Alcohol Mixture 100 =1000 ppm TWA

Component Information

Name CAS Number Weight % ACGIH Exposure

Limits:

OSHA - Vacated

PELs - Time

Weighted Ave

Other:

Natural Gasoline 8006-61-9 5 = 1500 mg/m³ STEL

= 300 ppm TWA
= 500 ppm STEL
= 900 mg/m³ TWA
Ethyl Alcohol 64-17-5 95 = 1000 ppm TWA =1000 ppm TWA
1900 mg/m³ TWA

Notes:

The manufacturer has voluntarily elected to reflect exposure limits contained in OSHA's 1989 air contaminants standard in its MSDS's, even though certain of those exposure limits were vacated in 1992.

MSDS ID NO.: 073010 Product name: Eco-Energy Denatured Alcohol

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DENATURED ALCOHOL IS A CLEAR, COLORLESS LIQUID WITH A HYDROCARBON ODOR. IT CONTAINS 95% ETHYL ALCOHOL. IT IS A VOLATILE AND EXTREMELY FLAMMABLE LIQUID THAT MAY CAUSE FLASH FIRES. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. NEVER SIPHON THIS PRODUCT BY MOUTH. IF SWALLOWED, THIS PRODUCT MAY GET SUCKED INTO THE LUNGS (ASPIRATED) AND CAUSE LUNG DAMAGE OR EVEN DEATH.

OSHA WARNING LABEL:

DANGER!
ASPIRATION (INADVERTENT SUCTION) OF LIQUID INTO THE LUNGS CAN PRODUCE CHEMICAL PNEUMONIA OR EVEN DEATH.

CONSUMER WARNING LABEL:

A CONSUMER WARNING LABEL IS NOT APPLICABLE FOR THIS PRODUCT.

Inhalation:

Prolonged breathing of high ethanol vapor concentrations can produce headache, dizziness, nausea, incoordination and impaired vision. Excessive overexposure can cause central nervous system depression, loss of consciousness, liver damage and death resulting from respiratory failure.

Ingestion:

Liquid ingestion can cause inebriation, headache, incoordination, gastrointestinal pain, nausea, and vomiting leading to central nervous system depression. Aspiration

(inadvertent suction) of liquid into the lungs must be avoided as even small quantities in the lungs can produce chemical pneumonitis, pulmonary edema/hemorrhage and even death.

Skin contact:

Liquid is practically non-irritating to the skin. Prolonged and repeated liquid contact can cause defatting and drying of the skin and can lead to irritation and/or dermatitis.

Eye contact:

Liquid may cause mild to severe irritation. Splash contact or high vapor concentrations can produce an immediate burning and stinging sensation.

Carcinogenic Evaluation:

Product information

Name IARC

Carcinogens:

NTP

Carcinogens:

ACGIH Carcinogens:

OSHA - Select

Carcinogens:

Eco-Energy Denatured Alcohol

Mixture

A1-Human Carcinogen A4-Non Classifiable

Notes:

The International Agency for Research on Cancer (IARC) has determined that there is sufficient evidence for the carcinogenicity of alcoholic beverages (ethanol) in humans (Group 1).

Component Information

Name IARC

Carcinogens:

NTP

Carcinogens:

ACGIH Carcinogens:

OSHA - Select

Carcinogens:

Natural Gasoline

8006-61-9

Monograph 45, 1989;

(Overall evaluation

upgraded from 3 to 2B with

supporting evidence from

other data relevant to the

evaluation of

carcinogenicity and its mechanisms)

MSDS ID NO.: 07302010 Product name: Eco-Energy Denatured Alcohol

Ethyl Alcohol
64-17-5
A2-Possible Human Carcinogen
A4 - Not Classifiable as a Human Carcinogen
Ethyl Alcohol
64-17-5
A2-Possible Human Carcinogen
A4 - Not Classifiable as a Human Carcinogen

Notes:

The International Agency for Research on Cancer (IARC) has determined that there is inadequate evidence for the carcinogenicity of gasoline in humans. IARC determined that limited evidence of carcinogenicity in animals exists. IARC's overall evaluation of gasoline, in spite of limited carcinogenicity evidence, has resulted in the IARC designation of gasoline as possibly carcinogenic to humans (Group 2B) because gasoline contains benzene.

4. FIRST AID MEASURES

Inhalation:

If affected, move person to fresh air. If breathing is difficult, administer oxygen. If not breathing or if no heartbeat, give artificial respiration or cardiopulmonary resuscitation (CPR). Immediately call a physician. If symptoms or irritation occur with any exposure, call a physician.

Skin contact:

Wash with soap and large amounts of water. Remove contaminated clothing. If symptoms or irritation occur, call a physician.

Ingestion:

If swallowed, do not induce vomiting and do not give liquids. Immediately call a physician.

Eye contact:

Flush eyes with large amounts of tepid water for at least 15 minutes. If symptoms or

irritation occur, call a physician.

Medical conditions aggravated by Pre-existing eye, skin, respiratory disorders and impaired liver function may be

exposure:

aggravated by overexposure to ethanol. Persons on disulfiram (antabuse) therapy

should be aware that the ethyl alcohol in the product is hazardous to them just as is

alcohol from any source. Disulfiram reactions (vomiting, headache and even

collapse) may follow ingestion of small amounts of alcohol.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media:

For small fires, Class B fire extinguishing media such as CO₂, dry chemical, foam (AFFF/ATC) or water spray can be used. For large fires, water spray, fog or foam (AFFT/ATC) can be used. Fire fighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.

Specific hazards:

This product has been determined to be a flammable liquid per the OSHA Hazard Communication Standard, and should be handled accordingly. Vapors may travel along the ground or be moved by ventilation and ignited by many sources such as pilot lights, sparks, electric motors, static discharge, or other ignition sources at locations distant from material handling. Flashback can occur along vapor trail.

For additional fire related information, see NFPA 30 or the North American Emergency Response Guide 127.

Special protective equipment for firefighters:

Flame is invisible in daylight. Avoid using straight water streams. Water may be ineffective in extinguishing low flash point fires, but can be used to cool exposed surfaces. Avoid excessive water spray application. Water spray and foam (AFFF/ATC) must be applied carefully to avoid frothing and from as far a distance as possible. Keep run-off water out of sewers and water sources.

Flash point:

Autoignition temperature:

<-5 F

No data available.

MSDS ID NO.: 073010 Product name: Eco-Energy Denatured Alcohol

Flammable limits in air - lower (%): 3.3

Flammable limits in air - upper (%): 19.0

NFPA rating:
HMIS classification:

Health: 1
Health: 1

Flammability: 3
Flammability: 3

Reactivity: 0
Reactivity: 0

Other: -Special: *See Section 8 for guidance in selection of personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Keep public away. Isolate and evacuate area. Shut off source if safe to do so.

Eliminate all ignition sources. Advise authorities and National Response Center (800424-

8802) if substance has entered a watercourse or sewer. Contain liquid with sand

or soil. Recover and return free product to proper containers. Use suitable

absorbent materials such as vermiculite, sand, or clay to clean up residual liquids.

7. HANDLING AND STORAGE

Handling:

Comply with all applicable EPA, OSHA, NFPA and consistent state and local requirements. Use appropriate grounding and bonding practices. Store in properly closed containers that are appropriately labeled and in a cool well-ventilated area. Do not expose to heat, open flames, strong oxidizers or other sources of ignition. Do not cut, drill, grind or weld on empty containers since they may contain explosive residues. Avoid skin contact. Exercise good personal hygiene including removal of soiled clothing and prompt washing with soap and water.

For use as a motor fuel only. Product should never be used as a solvent due to its flammable and potentially toxic properties. Siphoning by mouth can result in lung aspiration which can be harmful or fatal.

Portable containers of 12 gallons (45 liters) or less should never be filled while they are in or on a motor vehicle or marine craft. Static electric discharge can ignite fuel vapors when filling non-grounded containers or vehicles on trailers.

Containers should be placed on the ground. The nozzle spout must be kept in contact with the container before and during the entire filling operation. Use only approved containers. A buildup of static electricity can occur upon re-entry into a vehicle during fueling especially in cold or dry climate conditions. The charge is generated by the action of dissimilar fabrics (i.e., clothing and upholstery) rubbing across each other as a person enters/exits the vehicle. A flash fire can result from this discharge if sufficient flammable vapors are present. Therefore, do not get back in your vehicle while refueling. Cellular phones and other electronic devices may have the potential to emit electrical charges (sparks). Sparks in potentially explosive atmospheres (including fueling areas such as gas stations) could cause an explosion if sufficient flammable vapors are present. Therefore, turn off cellular phones and other electronic devices when working in potentially explosive atmospheres or keep devices inside your vehicle during refueling.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT

Engineering measures:

Local or general exhaust required in an enclosed area or when there is inadequate ventilation.

Respiratory protection:

Approved organic vapor chemical cartridge or supplied air respirators should be worn when significant vapors are generated. Observe respirator protection factor criteria cited in ANSI Z88.2. Self-contained breathing apparatus should be used for fire fighting.

Skin and body protection:

Use nitrile rubber, viton or PVA gloves for repeated or prolonged skin exposure.

Eye protection:

No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields.

MSDS ID NO.: 073010 Product name: Eco-Energy Denatured Alcohol

Hygiene measures:

No special protective clothing is normally required. Select protective clothing depending on industrial operations. Use mechanical ventilation equipment that is explosion-proof.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance: Colorless Liquid
Physical state (Solid/Liquid/Gas): Liquid
Substance type (Pure/Mixture): Mixture
Color: Clear
Odor: Very faint. Alcoholic
Molecular weight: 45
pH: Neutral
Boiling point/range (5-95%): 165-175 F
Melting point/range: Not determined.
Decomposition temperature: Not applicable.
Specific gravity: 0.79
Density: 6.6 lbs/gal
Bulk density: No data available.
Vapor density: 1.6
Vapor pressure: 43-47 mm Hg
Evaporation rate: No data available.
Solubility: Not determined
Solubility in other solvents: No data available.
Partition coefficient (n-octanol/water): 100%
VOC content(%): No data available.
Viscosity: No data available.

10. STABILITY AND REACTIVITY

Stability: The material is stable at 70 F, 760 mm pressure.
Polymerization: Will not occur.
Hazardous decomposition products: Carbon monoxide and carbon dioxide
Materials to avoid: Strong oxidizers such as nitrates, chlorates, peroxides.
Conditions to avoid: Excessive heat, sources of ignition and open flames.

11. TOXICOLOGICAL INFORMATION

Acute toxicity:
Product information

Name CAS Number Inhalation: Dermal: Oral:
Eco-Energy Denatured Alcohol Mixture 16,000-45,000 ppm
4-8 hr [Rat]
No data available 6-18 gm/kg [Rat]

MSDS ID NO.: 073010 Product name: Eco-Energy Denatured Alcohol

Intentional abuse, misuse or other massive exposure to ethanol may result in multiple organ damage and/or death. Chronic ingestion of large amounts of ethanol can cause cancer and damage to the liver, kidney, heart, brain, nervous system and stomach. Ethyl alcohol ingestion during pregnancy can adversely affect the unborn child. Studies in laboratory animals involving prolonged and repeated exposures have resulted in such effects as embryotoxicity, immunotoxicity and teratogenicity. Mutagenic effects have been reported in both in vitro and in vivo systems but usually at high dosages.

This product may contain natural gasoline at a level of >1.0%. Repeated dermal application has produced severe irritation and systemic toxicity in subacute toxicity studies. Some components of this product, i.e., paraffins and olefins, have been shown to produce a species specific sex hormonal dependent kidney lesion in male rats from repeated oral or inhalation exposure. Subsequent research has shown that the kidney damage develops via the formation of alpha-2uglobulin, a mechanism unique to the male rat. Humans do not form alpha-2u-globulin, therefore, the kidney effects resulting from this mechanism are not relevant in humans. Some components were found to be positive in a few mutagenicity tests while negative in the majority of others. The exact relationship between these results and human health is not known.

12. ECOLOGICAL INFORMATION

Ecotoxicity effects: No data available.

13. DISPOSAL CONSIDERATIONS

Cleanup Considerations:

This product as produced is not specifically listed as an EPA RCRA hazardous waste according to federal regulations (40 CFR 261). However, when discarded or disposed of, it may meet the criteria of an "characteristic" hazardous waste. This product could also contain benzene at >0.5 ppm and could exhibit the characteristics of "toxicity" as determined by the toxicity characteristic leaching procedure (TCLP). This material could become a hazardous waste if mixed or contaminated with a hazardous waste or other substance(s). It is the responsibility of the user to determine if disposal material is hazardous according to federal, state and local regulations.

14. TRANSPORT INFORMATION

49 CFR 172.101:
DOT:

Transport Information: This material when transported via US commerce would be regulated by DOT

Regulations.

Proper shipping name:
UN/Identification No:
Hazard Class:
Packing group:
DOT reportable quantity (lbs):

TDG (Canada):
Proper shipping name:
UN/Identification No:
Hazard Class:
Packing group:
Regulated substances:

Alcohols, N.O.S.
UN 19873II
Not applicable.

Alcohols, N.O.S.
UN 19873IINot applicable.

MSDS ID NO.: 073010 Product name: Eco-Energy Denatured Alcohol

15. REGULATORY INFORMATION

Federal Regulatory Information:

US TSCA Chemical Inventory Section 8(b):
This product and/or its components are listed on the TSCA Chemical Inventory.

OSHA Hazard Communication Standard:
This product has been evaluated and determined to be hazardous as defined in OSHA's Hazard Communication Standard.

EPA Superfund Amendment & Reauthorization Act (SARA):

SARA Section 302:
This product contains the following component(s) that have been listed on EPA's Extremely Hazardous Substance (EHS) List:

Name CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs
Natural Gasoline NA
Ethyl Alcohol NA

SARA Section 304:
This product contains the following component(s) identified either as an EHS or a

CERCLA Hazardous substance which in case of a spill or release may be subject to SARA reporting requirements:

Name CERCLA/SARA - Hazardous Substances and their Reportable Quantities
Natural Gasoline NA
Ethyl Alcohol NA

SARA Section 311/312: The following EPA hazard categories apply to this product:

Acute Health Hazard
Chronic Health Hazard
Fire Hazard

SARA Section 313: This product contains the following component(s) that may be subject to reporting on the Toxic Release Inventory (TRI) From R:

Name CERCLA/SARA 313 Emission reporting:
Natural Gasoline None
Ethyl Alcohol None

State and Community Right-To-Know Regulations:

The following component(s) of this material are identified on the regulatory lists below:

Natural Gasoline
Louisiana Right-To-Know:
California Proposition 65:
New Jersey Right-To-Know:
Pennsylvania Right-To-Know:
Massachusetts Right-To Know:
Florida substance List:
Rhode Island Right-To-Know:
Michigan critical materials register list:
Massachusetts Extraordinarily Hazardous Substances:
California - Regulated Carcinogens:
Pennsylvania RTK - Special Hazardous Substances:
New Jersey - Special Hazardous Substances:

Not Listed
Not Listed
sn 0957
Not Listed.
Present
Not Listed.
Toxic, Flammable
Not Listed.
Not Listed

Not ListedNot Listed

flammable - third degree

MSDS ID NO.: 073010 Product name: Eco-Energy Denatured Alcohol

New Jersey - Environmental Hazardous
Substances List:
Illinois - Toxic Air Contaminants
New York - Reporting of Releases Part 597 -
List of Hazardous Substances:

Ethyl Alcohol
Louisiana Right-To-Know:
California Proposition 65:

New Jersey Right-To-Know:
Pennsylvania Right-To-Know:
Massachusetts Right-To Know:
Florida substance List:
Rhode Island Right-To-Know:
Michigan critical materials register list:
Massachusetts Extraordinarily Hazardous
Substances:
California - Regulated Carcinogens:
Pennsylvania RTK - Special Hazardous
Substances:
New Jersey - Special Hazardous Substances:
New Jersey - Environmental Hazardous
Substances List:
Illinois - Toxic Air Contaminants
New York - Reporting of Releases Part 597 -
List of Hazardous Substances:

Canadian Regulatory Information:

SN 0957

Not Listed
Not Listed
Not Listed
developmental toxicity (when in alcoholic beverages); initial
date 10/1/87
sn 0844
Present
Teratogen
Not Listed.
Toxic, FlammableNot Listed.
Not Listed
Not Listed
Not Listed

flammable - third degree
Not Listed
Not Listed

Not Listed

Canada DSL/NDSL Inventory: This product and/or its components are listed either on the Domestic Substances List (DSL) or the Non Domestic Substance List (NDSL).

Name Canada - WHMIS: Classifications of Substances: Canada - WHMIS:
Ingredient Disclosure:
Natural Gasoline B2; D2A 1% (English Item 793, French Item 802)
Ethyl Alcohol B2; D2B 0.1% (English Item 684, French Item 805)

16. OTHER INFORMATION

Additional Information: No data available.

The information and recommendations contained herein are based upon tests believed to be reliable. However, Eco-Energy, Inc. does not guarantee their accuracy or completeness nor shall any of this information constitute a warranty, whether expressed or implied, as to the safety of the goods, the merchantability of the goods, or the fitness of the goods for a particular purpose. Adjustment to conform to actual conditions of usage maybe required. MPC assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

End of Safety Data Sheet